


SHOUT TS and GSM

*Compact, lightweight with
integrated panic button.*

-  Panic alarm
-  AES-256
-  Man-down alarm
-  Check-in
-  Up to 40 days



TrackIT

Shout TS and GSM - Personal Trackers

OVERVIEW

The Shout TS is a hand-held, global, two-way satellite messaging and personal tracking device. The GSM version is a dual-mode device utilising both Iridium and GSM networks to send location reports, two-way canned and free-text messages and emergency notifications

These devices both feature a high-resolution colour touch screen and menu options are displayed as icons for quick and easy access

PANIC ALARM

The unit includes an external panic button which can be found and activated by sliding the protective cover. These panic alerts are immediately displayed on the TrackIT panel and relevant users are automatically informed via text message and / or email

POWER

The units are designed with ultra-low power consumption electronics and can send a position report every hour for up to two months (about 1500 reports)

KEY FEATURES

- Low cost tracker and messaging device
- Ultra-low power consumption
- Automatic location reports (>1500 reports)
- Guarded panic alert button
- High resolution touchscreen
- Data logging
- AES-256 bit encryption (optional)
- Man-down alert capability for lone worker tracking
- In-built geo-fence alarm capability
- Real-time, pole-to-pole coverage
- Internal rechargeable battery using AC adaptor, computer USB port or solar charger
- Integrated motion sensor
- USB interface

INTEGRATION

The Shout Nano works seamlessly with the TrackIT panel, providing regular reports and has the option to save up to 10,000 reports to be sent at a later date



Global RadioData Communications Ltd (Head Office)
Wyevale Business Park, Wyevale Way
Hereford, HR4 7BS

UK: +44 (0)1432 373800
UAE: +97 152 849 3005
info@grcltd.net
www.grcltd.net

014683-DOC

SHOUT TS SPECIFICATIONS

Dimensions: 104mm x 58mm x 23mm
Weight: 204g
Battery: Rechargeable Li-Ion
1.95 A-Hr Single Cell
3.6V to 4.2V
I/O Interface: Standard USB
Software Interface: AT Commands through USB
Operating Temperature: -40°C to +85°C
Operating Humidity: < 75% RH
Operating Frequency: 1616 to 1626.5 MHz
GPS Frequency: 1575.42 MHz (L1 carrier)

SHOUT GSM SPECIFICATIONS

Dimensions: 104mm x 58mm x 23mm
Weight: 221g
Battery: Rechargeable Li-Ion
1.95 A-Hr Single Cell
3.6V to 4.2V
I/O Interface: Standard USB and Bluetooth
Software Interface: AT Commands through USB
Operating Temperature: -30°C to +70°C
Operating Humidity: < 75% RH
Operating Frequency: 1616 to 1626.5 MHz
GSM Frequency: 850 / 900 / 1800 / 1900 MHz
GPS Frequency: 1575.42 MHz (L1 carrier)

